



TECHNICAL DATA SHEET

PRODUCT FAMILY: 1531

ISSUE NUMBER: 120416/1

COMPOSITION

	<u>Weight</u>	<u>Thickness</u>
Adhesive	28gsm	28 micron
Liner	62gsm	55 micron

PRODUCT DESCRIPTION

A carrier free transfer tape with a synthetic rubber based permanent adhesive. The liner is a two sided siliconised release paper which overlaps at each edge to give a 'finger-lift' for easy removal.

APPLICATIONS

The industry standard tape for Continuous Stationery and Business Form applications. Flat wound rolls up to 2500M have performed with unmatched consistency on machine applied collators for many years.

ADHESIVE PROPERTIES

	<u>Typical values</u>	<u>Test method</u>
Peel Adhesion to steel (24 hour dwell)	800 N/M	PSTC 101
Shear Adhesion to steel (1kg; 25mm x 25mm)	100 hours	PSTC 107

THERMAL PROPERTY GUIDELINES

Service temperature range (short term)	0°C to 90°C
Application temperature range	10°C to 50°C

FOOD CONTACT INFORMATION

Based on supplier information the components of the adhesive conform to the compositional requirements of FDA 21 CFR 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

STORAGE

For guidance purposes we recommend that the product be used within 12 months of supply. The product should be stored in original closed cartons at non extreme ambient temperatures away from direct sources of heat and sunlight.

NOTE

Values given are average and should not be taken as a maximum or minimum for specification purposes.

Specific technical details, application information & suggested uses available

WARRANTY

All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance only. The Company is not bound contractually unless and until an order acknowledgement in writing is made and must be on the Company'

Essentra Packaging

Giltway
Nottingham, Nottinghamshire
NG16 2GT
United Kingdom

T +44 (0)115 9759000

F +44 (0)115 9759001

sales@essentrapackaging.co.uk